

ç | È | Ì | Á | È | Ì | D | Ì | H | È | F | È | Ì | Á | È | æ | Å | ð | O | { | [| ç | æ | ã | È | ~

T UVUÜÖÖWSVUÜKNMRV-050/110

{ | ç | ! | ^ | à | ~ | \ | ç | ! | Á | [| à , 5 | ð | ^ | Å | ð | Ì | € | Ó | F | I | D

WIDOK 3D



ÖÖË ÒÁÒÔÏ ÒÛÏ ÒÁÛ ÆÛÛ

GR Size	050-110
ES Execution	AS1
PAM Input PAM flange	80 B14
ACU1 Output hole shaft gear unit 1 (d)	25
VB1 Double input shaft gear unit 1	NO
ACU2 Output hole shaft gear unit 2 (d)	42
VB2 Double input shaft gear unit 2	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension gear unit 2 (d)	-
PFU Output flange position gear unit 2	-
AL2 Output hole shaft gear unit 2 (d)	NO
PAL Output shaft position gear unit 2	-
CAP Cover gear unit 2	NO
TIP Motor type	T-Three phase
GRA Motor size	080
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B14
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Default
MOR Terminal box cover position	1
A	120
AC	158
B	80
BB	12
BM	6
D	42
DM	19
E	40

F	M6x16
G1	155
H	127.5
H2	60
I	110
I2	50
L	272.5
LB	232.5
N2	43.5
PM	120
R	167.5
R2	84
T	50
TM	21.5
TT	45.3
Z	226



