


ÚÜZÒSýÖÖPÖK NMRV-110-100-112B5

WIDOK 3D



PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling
version PAM with sleeve

PRODUCT TYPE: NMRV

CONFIGURATION & DIMENSIONAL VALUES

| | |
|---------------------------------|------------|
| GR Size | 110 |
| RAP Ratio | 1 1/2 |
| PAM Input PAM flange | 100/112 B5 |
| ACU Output hole shaft (d) | 42 |
| VB Double input shaft | NO |
| TFU Output flange gear unit 2 | NO |
| DFU Output flange dimension (d) | - |
| PFU Output flange position | - |
| AL Output hole shaft (d) | NO |
| PAL Output shaft position | - |
| BR Torque arm | NO |
| PBR Torque arm position | - |
| CAP Cover | NO |
| TIP Motor type | NO |
| GRA Motor size | - |
| RAF Cooling | - |
| FC Motor execution | - |
| TF Break type | - |
| AF Brake power supply | - |
| COP Terminal box cover | - |
| CVE Fan cover | - |
| MOR Terminal box cover position | - |
| A | 170 |
| AC | - |
| B | 60 |
| B1 | 8 |
| BB | 12 |
| BM | 8 |
| BM1 | - |
| D | 42 |
| D1 | 28 |

PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling
version PAM with sleeve

PRODUCT TYPE: NMRV

CONFIGURATION & DIMENSIONAL VALUES

| | |
|-----|-----------|
| DM | 28 |
| DM1 | - |
| E | - |
| F | M10 |
| FF | - |
| G | 160 |
| G1 | 155 |
| H | 127.5 |
| I | 110 |
| K | 115 |
| KE | M10x18(8) |
| L | 144 |
| LB | - |
| LL | - |
| M | 165 |
| N | 130 |
| N1 | 74 |
| O | 14 |
| P | 200 |
| PM | 250 |
| PM1 | - |
| Q | 125 |
| R | 167.5 |
| S | 14.5 |
| T | 50 |
| T1 | 31 |
| TM | 31.3 |
| TM1 | - |
| TT | 45.3 |
| V | 85 |
| W | 45° |

2D VIEW PRA



PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling version PAM with sleeve

PRODUCT TYPE: NMRV

2D VIEW ACCESSORIES

