


T UVUÜÖÖWSVUÜKNMRV-075-80B14

## WIDOK 3D



## PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling  
version PAM with sleeve

## PRODUCT TYPE: NMRV

## CONFIGURATION & DIMENSIONAL VALUES

GR Size	075
PAM Input PAM flange	80 B14
ACU Output hole shaft (d)	28
VB Double input shaft	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension (d)	-
PFU Output flange position	-
AL Output hole shaft (d)	NO
PAL Output shaft position	-
BR Torque arm	NO
PBR Torque arm position	-
CAP Cover	NO
TIP Motor type	T-Three phase
GRA Motor size	080
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B14
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Standard
MOR Terminal box cover position	1
A	120
AC	158
B	50
B1	8
BB	8(10)
BM	6
BM1	6
D	28(35)
D1	24

## PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling  
version PAM with sleeve

**PRODUCT TYPE:** NMRV

## CONFIGURATION & DIMENSIONAL VALUES

DM	19
DM1	19
E	40
F	M8
FF	M6x16
G	112.5
G1	120
H	86
I	75
K	90
KE	M8x14(8)
L	112
LB	232.5
LL	272.5
M	115
N	95
N1	57
O	11.5
P	140
PM	120
PM1	120
Q	93
R	119
S	10
T	40
T1	27
TM	21.8
TM1	21.5
TT	31.3(38.3)
V	60
W	45°

# 2D VIEW PRA



# PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling version PAM with sleeve

## PRODUCT TYPE: NMRV

## 2D VIEW ACCESSORIES

