


MOTOREDUKTOR: NMRV-025-56B14

WIDOK 3D



PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling
version PAM with sleeve

PDF DATASHEET

PRODUCT TYPE: NMRV

CONFIGURATION & DIMENSIONAL VALUES

GR Size	025
PAM Input PAM flange	56 B14
ACU Output hole shaft (d)	11
VB Double input shaft	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension (d)	-
PFU Output flange position	-
AL Output hole shaft (d)	NO
PAL Output shaft position	-
BR Torque arm	NO
PBR Torque arm position	-
CAP Cover	NO
TIP Motor type	T-Three phase
GRA Motor size	056
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B14
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Standard
MOR Terminal box cover position	1
A	45
AC	115
B	-
B1	-
BB	4
BM	3
BM1	-
D	11
D1	-

PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling
version PAM with sleeve


PDF DATASHEET

PRODUCT TYPE: NMRV

CONFIGURATION & DIMENSIONAL VALUES

DM	9
DM1	-
E	-
F	-
FF	-
G	45
G1	50
H	35
I	25
K	34
KE	Ø 6.5 mm
L	42
LB	-
LL	-
M	55
N	45
N1	22.5
O	6
P	65
PM	80
PM1	-
Q	35.5
R	48
S	5
T	16
T1	-
TM	10.4
TM1	-
TT	12.8
V	22.5
W	10°

2D VIEW PRA



PRODUCT DESCRIPTION:

Worm geared motor fitted for motor coupling
version PAM with sleeve

PDF DATASHEET

PRODUCT TYPE: NMRV

2D VIEW ACCESSORIES

